

Q1.

| | | |
|-----------|---|-----|
| 2 (a) (i) | distance from a (fixed) point.....M1 in a specified direction A1 (Allow 1 mark for 'distance in a given direction') | |
| (ii) | (displacement from start is zero if) car at its starting position..... B1 | [3] |
| (b) (i)1 | $v^2 = u^2 + 2as$ $28^2 = 2 \times a \times 450$ (use of component of 450 scores no marks)..... C1 $a = 0.87 \text{ m s}^{-2}$ A1 (-1 for 1 sig. fig. but once only in the question) | [2] |
| (i)2 | $v = u + at$ or any appropriate equation $28 = 0.87t$ or appropriate substitution..... C1 $t = 32 \text{ s}$ A1 | [2] |

Q2.

| | | | |
|-----------|--|----------------|-----|
| 3 (a) (i) | scatter of points (about the line) | B1 | |
| (ii) | intercept (on t^2 axis) (note that answers must relate to the graph) | B1 | [2] |
| (b) (i) | gradient = $\Delta y / \Delta x = (100 - 0) / (10.0 - 0.6)$ gradient = $10.6 \text{ (cm s}^{-2}\text{)}$ (allow ± 0.2) (Read points to within $\pm \frac{1}{2}$ square. Allow 1 mark for 11 cm s^{-2} i.e. 2 sig fig, -1. Answer of 10 scores 0/2 marks) | C1 A1 | [2] |
| (ii) | $s = ut + \frac{1}{2}at^2$ so acceleration = $2 \times$ gradient acceleration = 0.212 m s^{-2} | B1 B1 B1 | [3] |
| Total | | | [7] |

Q3.

| | | | |
|---------|--|----|-----|
| (c) | horizontal velocity = 18 m s^{-1} | B1 | [1] |
| (d) (i) | correct shape of diagram (two sides of right-angled triangle with correct orientation) | B1 | |
| (ii) | angle = $41^\circ \rightarrow 48^\circ$ (allow trig. solution based on diagram) (for angle $38^\circ \rightarrow 41^\circ$ or $48^\circ \rightarrow 51^\circ$, allow 1 mark) | A2 | [3] |

Q4.

2 (a) 2.4 s A1 [1]

(b) in (b) and (c), allow answers as (+) or (–)
 recognises distance travelled as area under graph line C1
 height = $(\frac{1}{2} \times 2.4 \times 9.0) - (\frac{1}{2} \times 1.6 \times 6.0)$ C1
 = 6.0 m (allow 6 m) A1 [3]
 (answer 15.6 scores 2 marks
 answer 10.8 or 4.8 scores 1 mark)

alternative solution: $s = ut - \frac{1}{2}at^2$
 $= (9 \times 4) - \frac{1}{2} \times (9 / 2.4) \times 4^2$
 $= 6.0 \text{ m}$

(answer 66 scores 2 marks
 answer 36 or 30 scores 1 mark)

Q5.

2 (a) scalar B1
 scalar B1
 vector B1 [3]

(b) (i) 1 gradient (of graph) is the speed/velocity (can be scored here or in 2) B1
 initial gradient is zero B1 [2]

2 gradient (of line/graph) becomes constant B1 [1]

(ii) speed = $(2.8 \pm 0.1) \text{ m s}^{-1}$ A2 [2]
 (if answer $> \pm 0.1$ but $\leq \pm 0.2$, then award 1 mark)

(iii) curved line never below given line and starts from zero B1
 continuous curve with increasing gradient B1
 line never vertical or straight B1 [3]

Q6.

2 (a) e.g. initial speed is zero
 constant acceleration
 straight line motion
 (any two, one mark each) B2 [2]

(b) (i) $s = \frac{1}{2}at^2$
 $0.79 = \frac{1}{2} \times 9.8 \times t^2$ C1
 $t = 0.40 \text{ s}$ allow 1 SF or greater A1
 2 or 3 SF answer A1 [3]

(ii) distance travelled by end of time interval = 90 cm C1
 $0.90 = \frac{1}{2} \times 9.8 \times t^2$
 $t = 0.43 \text{ s}$ allow 2 SF or greater C1
 time interval = 0.03 s A1 [3]

(c) (air resistance) means ball's speed/acceleration is less M1
 length of image is shorter A1 [2]

Q7.

- 3 (a) evidence of use of area below the line
distance = 39 m (allow ± 0.5 m)
(if $> \pm 0.5$ m but ≤ 1.0 m, then allow 1 mark)

B1
A2 [3]

Q8.

- 1 (a) scalar has only magnitude
vector has magnitude and direction

B1
B1 [2]

- (b) kinetic energy, mass, power all three underlined

B1 [1]

- (c) (i) $s = ut + \frac{1}{2}at^2$
 $15 = 0.5 \times 9.81 \times t^2$
 $T = 1.7$ s

C1
A1 [2]

if $g = 10$ is used then -1 but only once on paper

- (ii) vertical component v_v :
 $v_v^2 = u^2 + 2as = 0 + 2 \times 9.81 \times 15$ or $v_v = u + at = 9.81 \times 1.7(5)$
 $v_v = 17.16$
resultant velocity: $v^2 = (17.16)^2 + (20)^2$
 $v = 26 \text{ ms}^{-1}$

C1
C1
A1 [3]

If $u = 20$ is used instead of $u = 0$ then 0/3
Allow the solution using:
initial (potential energy + kinetic energy) = final kinetic energy

- (iii) distance is the actual path travelled
displacement is the straight line distance between start and finish points (in that direction) / minimum distance

B1
B1 [2]

Q9.

- 2 (a) (i) base units of D :
 force: kg ms^{-2} B1
 radius: m velocity: ms^{-1} B1
 base units of D : $[F / (R \times v)] \text{ kg ms}^{-2} / (\text{m} \times \text{ms}^{-1})$ M1
 $= \text{kg m}^{-1} \text{s}^{-1}$ A0 [3]
- (ii) 1. $F = 6\pi \times D \times R \times v = [6\pi \times 6.6 \times 10^{-4} \times 1.5 \times 10^{-3} \times 3.7]$
 $= 6.9 \times 10^{-5} \text{ N}$ A1 [1]
2. $mg - F = ma$ hence $a = g - [F / m]$ C1
 $m = \rho \times V = \rho \times 4/3 \pi R^3 = (1.4 \times 10^{-5})$ M1
 $a = 9.81 - [6.9 \times 10^{-5} / \rho \times 4/3 \pi \times (1.5 \times 10^{-3})^3]$ (9.81 - 4.88) A1 [3]
 $a = 4.9(3) \text{ ms}^{-2}$
- (b) (i) $a = g$ at time $t = 0$ B1
 a decreases (as time increases) B1
 a goes to zero B1 [3]
- (ii) Correct shape below original line M1
 sketch goes to terminal velocity earlier A1 [2]

Q10.

- 2 (a) (i) $v = u + at$ C1
 $= 4.23 + 9.81 \times 1.51$ M1
 $= 19.0(4) \text{ ms}^{-1}$ (Allow 2 s.f.) A0 [2]
 (Use of $-g$ max 1/2. Use of $g = 10$ max 1/2. Allow use of 9.8. Allow 19 ms^{-1})
- (ii) either $s = ut + \frac{1}{2} at^2$ (or $v^2 = u^2 + 2as$ etc.) C1
 $= 4.23 \times 1.51 + 0.5 \times 9.81 \times (1.51)^2$ A1 [2]
 $= 17.6 \text{ m}$ (or 17.5 m)
 (Use of $-g$ here wrong physics (0/2))

Q11.

- 2 (a) (i) $v^2 = u^2 + 2as$ C1
 $= (8.4)^2 + 2 \times 9.81 \times 5$ A1 [2]
 $= 12.99 \text{ ms}^{-1}$ (allow 13 to 2 s.f. but not 12.9)
- (ii) $t = (v - u) / a$ or $s = ut + \frac{1}{2} at^2$ M1
 $= (12.99 - 8.4) / 9.81$ or $5 = 8.4t + \frac{1}{2} \times 9.81t^2$ A0 [1]
 $t = 0.468 \text{ s}$
- (b) reasonable shape M1
 suitable scale A1
 correctly plotted 1st and last points at (0,8.4) and (0.88 - 0.96,0)
 with non-vertical line at 0.47 s A1 [3]

Q12.

- 2 (a) (i) 1. distance of path / along line AB B1 [1]
2. shortest distance between AB / distance in straight line between AB or displacement from A to B B1 [1]
- (ii) acceleration = rate of change of velocity A1 [1]
- (b) (i) distance = area under line or $(v/2)t$ or $s = (8.8)^2 / (2 \times 9.81)$ C1
 $= 8.8 / 2 \times 0.90 = 3.96 \text{ m}$ or $s = 3.95 \text{ m} = 4(0) \text{ m}$ A1 [2]
- (ii) acceleration = $(-4.4 - 8.8) / 0.50$ C1
 $= (-) 26(4) \text{ m s}^{-2}$ A1 [2]
- (c) (i) the accelerations are constant as straight lines B1
- the accelerations are the same as same gradient or
no air resistance as acceleration is constant or
change of speed in opposite directions (one speeds up one slows down) B1 [2]
- (ii) area under the lines represents height
or KE at trampoline equals PE at maximum height B1
- second area is smaller / velocity after rebound smaller hence KE less B1
- hence less height means loss in potential energy A0 [2]

Q13.

- 3 (a) $v^2 = u^2 + 2as$ OR use of triangle etc C1
 $4.0^2 = 2 \times 9.8 \times s$ OR $s = \frac{1}{2} \times 4.0 \times 0.4$
 $s = 0.82 \text{ m}$ OR 0.80 m A1 [2]
- (b) $\Delta p = m(v - u)$ OR $p = mv$ C1
speeds are 4.2 m s^{-1} and 3.6 m s^{-1} C1
 $\Delta p = 0.045 (4.2 + 3.6)$ (2/4 only if speeds not added) C1
 $= 0.35 \text{ N s}$ A1 [4]
(1 mark only if only one speed used)
- (c) any time between 0.14 s and 0.17 s C1
force = $\Delta p / \Delta t = 0.35 / 0.14$ (allow e.c.f.)
 $= 2.5 \text{ N}$ A1 [2]

Q14.

- 1 (a) (i) acceleration (allow a definition of acceleration)..... B1
- (ii) the velocity is decreasing or force/acceleration is in negative direction – accept 'body is decelerating'/'slowing down' B1 [2]
- (b) (i) e.g. separation of dots becomes constant/does not continue to increase (must make a reference to the diagram) B1
- (ii)1 distance = 132 cm..... B1
- (ii)2 at constant speed, distance travelled in 0.1 s = 25 cm (allow ± 1 cm)..... C1
distance = 132 + (4 x 25)
= 232 cm A1 [4]
- (c) $s = ut + \frac{1}{2}at^2$
 $1.6 = \frac{1}{2} \times 9.8 \times t^2$ (allow $g = 10 \text{ m s}^{-2}$ C1
 $t = 0.57 \text{ s}$ C1
hence 6 photographs ('bald' answer scores 2 marks only)..... A1 [3]

Q15.

- 3 (a) constant gradient/straight line B1 [1]
- (b) (i) 1.2 s A1
- (ii) 4.4 s A1 [2]
- (c) either use of area under line or $h = \text{average speed} \times \text{time}$ C1
 $h = \frac{1}{2} \times (4.4 - 1.2) \times 32$ C1
= 51.2 m A1 [3]
- (allow 2/3 marks for determination of $h = 44 \text{ m}$ or $h = 58.4 \text{ m}$
allow 1/3 marks for answer 7.2 m)
- (d) $\Delta p = m\Delta v$ OR $p = mv$ C1
= 0.25 x (28 + 12) C1
= 10 N s A1 [3]
- (answer 4 N s scores 2/3 marks)

- 3 (e) (i) total/sum momentum before = total/sum momentum after B1
in any closed system B1 [2]
- (ii) either the system is the ball and Earth B1
momentum of Earth changes by same amount B1
but in the opposite direction B1
- or Ball is not an isolated system/there is a force on the ball (B1)
Gravitational force acts on the ball (B1)
causes change in momentum/law does not apply here (B1) [3]
(if explains in terms of air resistance, allow first mark only)

Q16.

- 3 (a) change in velocity/time (taken) B1 [1]
- (b) velocity is a vector/velocity has magnitude & direction B1
direction changing so must be accelerating B1 [2]

Q17.

- 4 (a) (i) use of tangent at time $t = 0$ B1
acceleration = $42 \pm 4 \text{ cm s}^{-2}$ A1 [2]
- (ii) use of area of loop B1
distance = $0.031 \pm 0.001 \text{ m}$ B2 [3]
allow 1 mark if $0.031 \pm 0.002 \text{ m}$

Q18.

- 2 (a) uses a tangent (anywhere), not a single point C1
draws tangent at correct position B1
acceleration = 1.7 ± 0.1 A2 [4]
(outside 1.6 \rightarrow 1.8 but within 1.5 \rightarrow 1.9, allow 1 mark)
- (b) (i) because slope (of tangent of graph) is decreasing M1
acceleration is decreasing A1 [2]
- (ii) e.g. air resistance increases (with speed) B1 [1]
(angle of) slope of ramp decreases
- (c) (i) scatter of points about line B1 [1]
(ii) intercept / line does not go through origin B1 [1]

Q19.

2 (a) $3.5 T$ B1 [1]

(b) (i) distance = average speed \times time (however expressed)
= 14 m C1
A1 [2]

(ii) distance = $5.6 \times (T - 5)$ (or $3.5T - 14$) A1 [1]

(c) $3.5T = 14 + 5.6(T - 5)$ C1
 $T = 6.7 \text{ s}$ A1 [2]

(d) (i) acceleration = $(5.6 / 5) = 1.12 \text{ m s}^{-2}$ C1
force = ma C1
= 75 N A1 [3]

(ii) power = (force \times speed) = $\{75 + 23\} \times 4.5$ C1
= 440 W A1 [2]
(allow 1/2 for 234 W, 0/2 for 338 W or 104 W)

Q20.

2 (a) (i) $v^2 = 2as$ C1
 $v^2 = 2 \times 0.85 \times 9.8 \times 12.8$ A1 [2]
 $v = 14.6 \text{ m s}^{-1}$

(ii) time = $29.3 / 14.6$ C1
= 2.0 s A1 [2]
(any acceleration scores 0 marks; allow 1 s.f.)

(b) either $60 \text{ km h}^{-1} = 16.7 \text{ m s}^{-1}$
or $14.6 \text{ m s}^{-1} = 53 \text{ km h}^{-1}$
or $22.1 \text{ m s}^{-1} = 79.6 \text{ km h}^{-1}$ M1
so driving within speed limit A1
but reaction time is too long / too slow B1 [3]

Q21.



- 2 (a) (i) (air) resistance increases with speedM1
 resultant / accelerating force decreases A1 [2]
- (ii) either (air) resistance is zero
 or weight / gravitational force is only force B1 [1]
- (b) use of gradient of a tangentM1
 acceleration = $1.9 \pm 0.2 \text{ m s}^{-2}$ A2 [3]
 (for values $> \pm 0.2$ but ≤ 0.4 , allow 1 mark)
 (answer 3.3 m s^{-2} scores no marks)
- (c) (i) 1 weight = $90 \times 9.8 = 880 \text{ N}$ A1 [1]
 (use of $g = 10 \text{ m s}^{-2}$ then deduct mark but once only in the Paper)
 2 accelerating force = $90 \times 1.9 = 170 \text{ N}$... (allow ecf) A1 [1]
- (ii) resistive force = $880 - 170 = 710 \text{ N}$ A1 [1]
 (allow ecf but only if resistive force remains positive)
- [Total: 9]

Q22.

- 3 (a) (i) speed = 4.0 m s^{-1} ... (allow 1 s.f.) A1 [1]
- (ii) $v^2 = 2gh$
 $= 2 \times 9.8 \times 1.96$ M1
 $v = 6.2 \text{ m s}^{-1}$ A0 [1]
 (use of $g = 10 \text{ m s}^{-2}$ loses the mark)
- (b) correct basic shape with correct directions for vectorsM1
 speed = $(7.4 \pm 0.2) \text{ m s}^{-1}$ A1
 at $(33 \pm 2)^\circ$ to the vertical A1 [3]
 (for credit to be awarded, speed and angle must be correct on the diagram – not calculated)
- (c) (i) either $v^2 = 2 \times 9.8 \times 0.98$ or $v = 6.2 / \sqrt{2}$ C1
 speed = 4.4 m s^{-1} A1 [2]
 (allow calculation of $t = 0.447 \text{ s}$, then $v = 4.4 \text{ m s}^{-1}$)
- (ii) 1 momentum = mv C1
 change in momentum = $0.034 (6.2 + 4.4)$ C1
 $= 0.36 \text{ kg m s}^{-1}$ A1 [3]
 (use of $0.034 (6.2 - 4.4)$ loses last two marks)
 2 force = $\Delta p / \Delta t$ (however expressed) C1
 $= \frac{0.36}{0.12}$
 $= 3.0 \text{ N}$ (allow 1 s.f.) A1 [2]
- [Total: 12]

Q23.

- 2 (a) (i) horizontal speed constant at 8.2 m s^{-1}
vertical component of speed = $8.2 \tan 60^\circ$
= 14.2 m s^{-1} C1
M1
A0 [2]
- (ii) $14.2^2 = 2 \times 9.8 \times h$ (using $g = 10$ then -1)
vertical distance = 10.3 m C1
A1 [2]
- (iii) time of descent = $14.2 / 9.8 = 1.45 \text{ s}$ C1
 $x = 1.45 \times 8.2$
= 11.9 m A1 [2]
- (b) (i) smooth path curved and above given path
hits ground at more acute angle M1
A1 [2]
- (ii) smooth path curved and below given path
hits ground at steeper angle M1
A1 [2]

Q24.

- 2 (a) (i) $V_H = 12.4 \cos 36^\circ (= 10.0 \text{ m s}^{-1})$ C1
distance = 10.0×0.17
= 1.7 m A1 [2]
- (ii) $V_V = 12.4 \sin 36^\circ (= 7.29 \text{ m s}^{-1})$ C1
 $h = 7.29 \times 0.17 - \frac{1}{2} \times 9.81 \times 0.17^2$ C1
= 1.1 m A1 [3]
- (b) smooth curve with ball hitting wall below original
smooth curve showing rebound to ground with correct reflection at wall B1
B1 [2]

Q25.

- 4 (a) acceptable straight line drawn (touching every point) B1 [1]
- (b) the distance fallen is not d C1
 d is the distance fallen plus the diameter of the ball A1 [2]
(d is not measured to the bottom of the ball' scores 2/2)
- (c) (i) diameter: allow $1.5 \pm 0.5 \text{ cm}$ (accept one SF) A1 [1]
no ecf from (a)
- (ii) gradient = $4.76, \pm 0.1$ with evidence that origin has not been used C1
gradient = $g / 2$ C1
 $g = 9.5 \text{ m s}^{-2}$ A1 [3]

Q26.

- 3 (a) (i) horizontal velocity = $15 \cos 60^\circ = 7.5 \text{ m s}^{-1}$ A1 [1]
(ii) vertical velocity = $15 \sin 60^\circ = 13 \text{ m s}^{-1}$ A1 [1]
- (b) (i) $v^2 = u^2 + 2as$
 $s = (13)^2 / (2 \times 9.81) = 8.6(1) \text{ m}$ A1 [1]
using $g = 10$ then max. 1
- (ii) $t = 13 / 9.81 = 1.326 \text{ s}$ or $t = 9.95 / 7.5 = 1.327 \text{ s}$ A1 [1]
- (iii) velocity = $6.15 / 1.33$ M1
 $= 4.6 \text{ m s}^{-1}$ A0 [1]
- (c) (i) change in momentum = $60 \times 10^{-3} [-4.6 - 7.5]$ C1
 $= (-)0.73 \text{ N s}$ A1 [2]
- (ii) final velocity / kinetic energy is less after the collision or
relative speed of separation < relative speed of approach
hence inelastic M1
A0 [1]

Q27.

- 1 (a) average velocity = $540 / 30$ C1
 $= 18 \text{ m s}^{-1}$ A1 [2]
- (b) velocity zero at time $t = 0$ B1
positive value and horizontal line for time $t = 5 \text{ s}$ to 35 s B1
line / curve through $v = 0$ at $t = 45 \text{ s}$ to negative velocity B1
negative horizontal line from 53 s with magnitude less than positive value and
horizontal line to time = 100 s B1 [4]

Q28.

- 2 (a) 1. constant velocity / speed B1 [1]
2. *either* constant / uniform decrease (in velocity/speed)
or constant rate of decrease (in velocity/speed) B1 [1]
- (b) (i) distance is area under graph for both stages C1
stage 1: distance $(18 \times 0.65) = 11.7$ (m)
stage 2: distance $= (9 \times [3.5 - 0.65]) = 25.7$ (m)
total distance $= 37.4$ m
(-1 for misreading graph)
{for stage 2, allow calculation of acceleration (6.32 m s^{-2})
and then $s = (18 \times 2.85) + \frac{1}{2} \times 6.32 (2.85)^2 = 25.7$ m} A1 [2]
- (ii) *either* $F = ma$ or $E_k = \frac{1}{2}mv^2$ C1
 $a = (18 - 0)/(3.5 - 0.65)$ $E_k = \frac{1}{2} \times 1250 \times (18)^2$ C1
- $F = 1250 \times 6.3 = 7900 \text{ N}$ or $F = \frac{1}{2} \times 1250 \times (18)^2 / 25.7 = 7900 \text{ N}$ A1 [3]
or initial momentum $= 1250 \times 18$ (C1)
 $F = \text{change in momentum} / \text{time taken}$ (C1)
 $F = (1250 \times 18) / 2.85 = 7900$ (A1)
- (c) (i) stage 1: *either* half / less distance as speed is half / less
or half distance as the time is the same
or sensible discussion of reaction time B1 [1]
- (ii) stage 2: *either* same acceleration and $s = v^2 / 2a$ or v^2 is $\frac{1}{4}$
 $\frac{1}{4}$ of the distance B1 [2]

Q29.

- 1 (a) units for D identified as kg m s^{-2} M1
all other units shown: units for A : m^2 units for v^2 : $\text{m}^2 \text{ s}^{-2}$ units for ρ : kg m^{-3}
- $C = \frac{\text{kg m s}^{-2}}{\text{kg m}^{-3} \text{ m}^2 \text{ m}^2 \text{ s}^{-2}}$ with cancelling / simplification to give C no units A1 [2]
- (b) (i) straight line from (0,0) to (1,9.8) \pm half a square B1 [1]
- (ii) $\frac{1}{2}mv^2 = mgh$ or using $v^2 = 2as$ C1
 $v = (2 \times 9.81 \times 1000)^{1/2} = 140 \text{ m s}^{-1}$ A1 [2]
- (c) (i) weight = drag (D) (+ upthrust) B1 [1]
Allow mg or W for weight and D or expression for D for drag
- (ii) 1. $mg = 1.4 \times 10^{-5} \times 9.81$ C1
 $1.4 \times 10^{-5} \times 9.81 = 0.5 \times 0.6 \times 1.2 \times 7.1 \times 10^{-6} \times v^2$ M1
 $v = 7.33 \text{ m s}^{-1}$ A0 [2]
2. line from (0,0) correct curvature to a horizontal line at velocity of 7 m s^{-1} M1
line reaches 7 m s^{-1} between 1.5 s and 3.5 s A1 [2]

Q30.

- 3 (a) (i) power is the rate of doing work or power = work done / time (taken) or
power = energy transferred / time (taken) B1 [1]
- (b) (i) as the speed increases drag / air resistance increases B1
resultant force reduces hence acceleration is less B1
constant speed when resultant force is zero B1 [3]
(allow one mark for speed increases and acceleration decreases)
- (ii) force from cyclist = drag force / resistive force B1
 $P = 12 \times 48$ M1
 $P = 576 \text{ W}$ A0 [2]
- (iii) tangent drawn at speed = 8.0 m s^{-1} M1
gradient values that show acceleration between 0.44 to 0.48 m s^{-2} A1 [2]
- (iv) $F - R = ma$ C1
 $600 / 8 - R = 80 \times 0.5$ [using $P = 576$] $576 / 8 - R = 80 \times 0.5$ C1
 $R = 75 - 40 = 35 \text{ N}$ $R = 72 - 40 = 32 \text{ N}$ A1 [3]
- (v) at 12 m s^{-1} drag is 48 N , at 8 m s^{-1} drag is 35 or 32 N
 R / v calculated as 4 and 4 or 4.4
and consistent response for whether R is proportional to v or not B1 [1]

Q31.

- 3 (a) (i) velocity = rate of change of displacement
OR displacement change / time (taken) A1 [1]
- (ii) acceleration = rate of change of velocity
OR change in velocity / time (taken) A1 [1]
- (b) (i) initial constant velocity as straight line / gradient constant B1
middle section deceleration/ speed / velocity decreases / slowing down as
gradient decreases B1
last section lower velocity (than at start) as gradient (constant and) smaller B1 [3]
[special case: all three stages correct descriptions but no reasons 1/3]
- (ii) velocity = $45 / 1.5 = 30 \text{ m s}^{-1}$ A1 [1]
- (iii) velocity at 4.0 s is $(122 - 98) / 2.0 = 12 \text{ (m s}^{-1}\text{)}$ (allow 12 to 13) B1
acceleration = $(12 - 30) / 2.5 = -7.2 \text{ m s}^{-2}$ (if answer not this value then
comment needed to explain why, e.g. difficulty in drawing tangent) A1 [2]
- (iv) $F = ma$ C1
 $= (-)1500 \times 7.2 = (-)11000 \text{ (10800) N}$ A1 [2]