UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the May/June 2007 question paper

9702 PHYSICS

9702/04

Paper 4 (A2 Structures Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the May/June 2007 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



UNIVERSITY of CAMBRIDGE International Examinations

	Page 2		2	Mark Scheme		Paper 04	
				GCE A/AS LEVEL – May/June 2007	Syllabus 9702		
1	(a)	(reថ្	gion o	f space) where a <u>mass</u> experiences a force		B1	[1]
	(b)	(i)	ΔE_{P}	ntial energy = (–)GMm / x = GMm/2R – GMm/3R Mm/6R		C1 M1 A0	[2]
		(ii)		$\frac{1}{2}m (7600^2 - 7320^2)$ 09 × 10 ⁶)m		M1 A0	[1]
	(c)	(i)		imes 10 ⁶ = (6.67 $ imes$ 10 ⁻¹¹ <i>M</i>)/(6 $ imes$ 3.4 $ imes$ 10 ⁶) 6.39 $ imes$ 10 ²³ kg		C1 A1	[2]
		(ii)	rock	no energy dissipated due to friction with <u>atmosphere/a</u> et is outside atmosphere nfluenced by another planet etc.	ir	B1	[1]
2	(a)	òr r kine	nolec etic er	ng,) bonds between molecules are broken/weakened ules further apart/are able to slide over one another nergy unchanged so no temperature change energy increased/changed so energy required		B1 B1 B1	[3]
	(b)			energy/heat required to convert unit mass of solid to liq hange in temperature/ at its normal boiling point	uid	M1 A1	[2]
	(c)	(i) (ii)	= 67 67.2 L = 3 more	mal energy lost by water = $0.16 \times 4.2 \times 100$.2 kJ = $0.205 \times L$ 328 kJ kg ⁻¹ e energy (than calculated) melts ice		C1 C1 A1 M1	[3]
3	(a)		d stre	calculated) <i>L</i> is lower than the accepted value ngth = potential gradient ign OR directions discussed		A1 M1 A1	[2] [2]
	(b)	area is 21.2 cm ² \pm 0.4 cm ² (<i>if outside</i> \pm 0.4 cm ² <i>but within</i> \pm 0.8 cm ² , allow 1 mark) 1.0 cm ² represents ($1.0 \times 10^{-2} \times 2.5 \times 10^{3}$ =) 25 V potential difference = 530 V			C2 C1 A1	[4]	
	(c)	$\frac{1}{2}mv^2 = qV$ $\frac{1}{2} \times 9.1 \times 10^{-31} \times v^2 = 1.6 \times 10^{-19} \times 530$ $v = 1.37 \times 10^7 \text{ ms}^{-1}$			C1 A1	[2]	
	(d)	(i)	d = ()		B1	[1]
			acce som (<i>any</i>	eleration decreases then increases e quantitative analysis (e.g. minimum at 4.0 cm) suggestion that acceleration becomes zero or that the eleration scores 0/2)	ere is a	B1 B1	[2]

	Page 3		Mark Scheme	Syllabus	Paper	
	-		GCE A/AS LEVEL – May/June 2007	9702	04	
4	N _S /	/N _P =	tput = 9/√2 or peak input = 230√2 V _S /V _P 8 → 140 turns		C1 C1 A1	[3]
	(b) (i)		diodes correctly positioned regardless of output polariting correct output polarity (<i>all 'point to left'</i>)	ţy	M1 A1	[2]
	(ii)	сара	acitor shown in parallel with R		B1	[1]
	(c) (i)	time	t_1 to time t_2		B1	[1]
	(ii)		ch: same peak values e reduced and reasonable shape		M1 A1	[2]
5	(a) (i)	pack	ket/discrete quantity/quantum (of energy) of e.m. radiat	ion	B1	[1]
	(ii)	or E	er $E = (6.63 \times 10^{-34} \times 3 \times 10^8)/(350 \times 10^{-9})$ $F = (6.63 \times 10^{-34} \times 8.57 \times 10^{14})$ $5.68 \times 10^{-19} \text{ J}$		M1 A0	[1]
	(iii)	0.5			B1	[1]
	(b) (i)	to ca	rgy of photon ause emission of electron <u>from surface</u>		M1	
		eithe	er with zero k.e or photon energy is minimum		A1	[2]
	(ii)	phot	ect conversion eV \rightarrow J or J \rightarrow eV seen once on energy must be greater than work function nm wavelength and potassium metal		B1 C1 A1	[3]
6	of a	a nucl	ty of decay eus per unit time mark for $A = \lambda N$, with symbols explained)		M1 A1	[2]
	(b) (i)		n2/(28 × 365 × 24 × 3600) 85 × 10 ⁻¹⁰ s ⁻¹		C1 A1	[2]
	(ii)	N = = 8.1 mas	$(-)\lambda N$ (6.4 × 10 ⁹)/(7.85 × 10 ⁻¹⁰) 15 × 10 ¹⁸ s = (8.15 × 10 ¹⁸ × 90)/(6.02 × 10 ²³) (e.c.f. for value of N 22 × 10 ⁻³ g	V)	C1 C1 C1 A1	[4]
	(iii)	volu	me = $(1.22 \times 10^{-3}/2.54 =) 4.8 \times 10^{-4} \text{ cm}^{-3}$		A1	[1]
	oro	dust c	ery small volume of Strontium-90 has high activity an be highly radioactive g in dust presents health hazard		B1 B1	[2]

	Page 4	4 Mark Scheme		Syllabus	Paper	
	J -		GCE A/AS LEVEL – May/June 2007	9702	04	
7	(a) (i)	as m e.m. caus ener	lations are <u>damped</u> /amplitude decreases hagnet moves, flux is cut by coil f./current is induced in the coil sing energy loss in load OR force on magnet gy is derived from oscillations of magnet force opposes motion of magnet		B1 B1 B1 B1 B1	[5]
	(ii)		0.60 s = 2π/T) = 10.5 rad s ⁻¹		C1 A1	[2]
	• •		inusoidal wave with period unchanged or slightly smal ial displacement, less damping	ler	M1 A1	[2]
	(c) (i)		ch: general shape – peaked curve α at ω_0 and amplitude never zero		M1 A1	[2]
	(ii)	reso	nance		B1	[1]
	(iii)	avoi	ul: e.g. child on swing, microwave oven heating d: e.g. vibrating panels, vibrating bridges credit, stated example must be put in context)		B1 B1	[2]
Se	ction B					
8	(a) e.g	infini zero infini infini	ite (voltage) gain ite input impedance output impedance ite bandwidth ite slew rate <i>three, 1 each</i>)		В3	[3]
	(b) (i)	nega	ative (feedback)		B1	[1]
	(ii)	1 ga	ain (= 5.8/0.069) = 84		B1	[1]
	(ii)	84 =	ain = 1 + 120/X 1 + 120/X 1.45 kΩ		C1 A1	[2]
	(iii)	gain	increases OR bandwidth reduced OR output increase	S	B1	[1]

	Page 5		Mark Scheme	Syllabus	Paper 04	
			GCE A/AS LEVEL – May/June 2007	9702		
9	(a)	different giving 'sl	eam directed through body onto detector (plate) tissues absorb/attenuate beam by different amounts hadow' image of structures er detail e.g. comment re sharpness or contrast		B1 B1 B1 B1	[4]
	(b)	CT scan these bu series of so that 3 image ca	hage is flat OR 2-dimensional (1) in takes many images of a slice at different angles (1) uild up an image of a slice through the body (1) f images of slices is made (1) BD image can be built up (1) an then be rotated (1) for each point, max 5		В5	[5]
10	(a)	graph dr	values of 2, 5, 10, 15 and 4 (– <i>1 each error</i>) rawn as a series of steps ccurring at correct times		B2 M1 A1	[4]
	(b)	•	more frequently number of bits		B1 B1	[2]
11	(a)	both amp	or and oscillator identified plifiers identified correctly d parallel-to serial converter identified		B1 B1 B1	[3]
	(b)	monitors switches	er at cellular exchange s signal strength s call from one base station to another ain maximum signal strength		B1 B1 B1 B1	[4]