



**GCE**

**Physics A**

**H556/03: Unified physics**

Advanced GCE

**Mark Scheme for November 2020**

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

© OCR 2020

Here are the subject specific instructions for this question paper.

## CATEGORISATION OF MARKS

The marking schemes categorise marks on the MACB scheme.

- B** marks    These are awarded as independent marks, which do not depend on other marks. For a **B**-mark to be scored, the point to which it refers must be seen specifically in the candidate's answers.
- M** marks    These are method marks upon which **A**-marks (accuracy marks) later depend. For an **M**-mark to be scored, the point to which it refers must be seen in the candidate's answers. If a candidate fails to score a particular **M**-mark, then none of the dependent **A**-marks can be scored.
- C** marks    These are compensatory method marks which can be scored even if the points to which they refer are not written down by the candidate, providing subsequent working gives evidence that they must have known it. For example, if an equation carries a **C**-mark and the candidate does not write down the actual equation but does correct working which shows the candidate knew the equation, then the **C**-mark is given.
- A** marks    These are accuracy or answer marks, which either depend on an **M**-mark, or allow a **C**-mark to be scored.

## SIGNIFICANT FIGURES

If the data given in a question is to 2 SF, then allow an answer to 2 or more significant figures.

If an answer is given to fewer than 2 SF, then penalise once only in the entire paper.

Any exception to this rule will be mentioned in the Additional Guidance.

## Annotations

Annotation		Meaning
	Correct response	Used to indicate the point at which a mark has been awarded ( <b>one tick per mark awarded</b> ).
	Incorrect response	Used to indicate an incorrect answer or a point where a mark is lost.
<b>AE</b>	Arithmetic error	Do not allow the mark where the error occurs. Then follow through the working/calculation giving full subsequent ECF if there are no further errors.
<b>BOD</b>	Benefit of doubt given	Used to indicate a mark awarded where the candidate provides an answer that is not totally satisfactory, but the examiner feels that sufficient work has been done.
<b>BP</b>	Blank page	Use BP on additional page(s) to show that there is no additional work provided by the candidates.
<b>CON</b>	Contradiction	No mark can be awarded if the candidate contradicts himself or herself in the same response.
<b>ECF</b>	Error carried forward	Used in <u>numerical answers only</u> , unless specified otherwise in the mark scheme. Answers to later sections of numerical questions may be awarded up to full credit provided they are consistent with earlier incorrect answers. Within a question, ECF can be given for AE, TE and POT errors but not for XP.
<b>L1</b>	Level 1	L1 is used to show 2 marks awarded and L1 <sup>^</sup> is used to show 1 mark awarded.
<b>L2</b>	Level 2	L2 is used to show 4 marks awarded and L2 <sup>^</sup> is used to show 3 marks awarded.
<b>L3</b>	Level 3	L3 is used to show 6 marks awarded and L3 <sup>^</sup> is used to show 5 marks awarded.
<b>POT</b>	Power of 10 error	This is usually linked to conversion of SI prefixes. Do not allow the mark where the error occurs. Then follow through the working/calculation giving ECF for subsequent marks if there are no further errors.
<b>SEEN</b>	Seen	To indicate working/text has been seen by the examiner.
<b>SF</b>	Error in number of significant figures	Where more SFs are given than is justified by the question, do not penalise. Fewer significant figures than necessary will be considered within the mark scheme. <b>Penalised only once in the paper.</b>
<b>TE</b>	Transcription error	This error is when there is incorrect transcription of the correct data from the question, graphical read-off, formulae booklet or a previous answer. Do not allow the relevant mark and then follow through the working giving ECF for subsequent marks.
<b>XP</b>	Wrong physics or equation	Used in <u>numerical answers only</u> , unless otherwise specified in the mark scheme. Use of an incorrect equation is wrong physics even if it happens to lead to the correct answer.
<b>^</b>	Omission	Used to indicate where more is needed for a mark to be awarded (what is written is not wrong but not enough).

Abbreviations, annotations and conventions used in the detailed Mark Scheme (to include abbreviations and subject-specific conventions).

<b>Annotation</b>	<b>Meaning</b>
/	alternative and acceptable answers for the same marking point
<b>Reject</b>	Answers which are not worthy of credit
<b>Not</b>	Answers which are not worthy of credit
<b>Ignore</b>	Statements which are irrelevant
<b>Allow</b>	Answers that can be accepted
()	Words which are not essential to gain credit
—	Underlined words must be present in answer to score a mark
<b>ECF</b>	Error carried forward
<b>AW</b>	Alternative wording
<b>ORA</b>	Or reverse argument

**General rule:** For substitution into an equation, allow any subject – unless stated otherwise in the guidance

Question			Answer	Marks	Guidance
1	(a)	(i)	$F = QE = QV/d$ or $E = 5(.0) \times 10^4 \text{ (Vm}^{-1}\text{)}$ $F = 9.0 \times 10^{-9} \times 4000 / 8.0 \times 10^{-2} (= 4.5 \times 10^{-4} \text{ N})$	<b>C1</b>  <b>A1</b>	$F = 5.0 \times 10^4 \times 9.0 \times 10^{-9}$
		(ii)	weight; arrow vertically downwards  tension; arrow upwards in direction of string  electric (force); arrow horizontally to the <u>right</u> (not along dotted line)	<b>B1 x 2</b>	All correct, 2 marks; 2 correct, 1 mark 1 mark maximum if more than 3 arrows are drawn <b>Ignore</b> position of arrows  <b>Allow W or 0.030(N) (not gravity or g)</b>  <b>Allow T</b>  <b>Allow F or E or <math>4.5 \times 10^{-4}</math>(N) or electrostatic</b> <b>Ignore</b> repulsion or attraction <b>Not</b> electric field / electric field strength / electromagnetic
		(iii)	$Wx = Fl$  0.03 x  $= 4.5 \times 10^{-4} \times 120$ or $= 4.5 \times 10^{-4} \times 1.2$  $x = 1.8 \text{ cm}$ or $x = 0.018 \text{ m}$	<b>M1</b>  <b>M1</b>  <b>A0</b>	<b>Allow</b> any valid alternative approach e.g. M1 deflection angle $\theta = 1^\circ$ M1 $x = 120\sin\theta$  1 mark for each side of the equation

	<b>(b)</b>	<p>Electric force/field (strength) increases</p> <p>Ball deflected further from vertical / moves to the right / touches negative plate</p> <p>Ball acquires the charge of the (negative) plate when it touches</p> <p>(Oscillates because) constantly repelled from (oppositely) charged plate</p>	<p><b>B1</b></p> <p><b>B1</b></p> <p><b>B1</b></p> <p><b>B1</b></p>	<p>Must be clear which force is increasing</p> <p>Must have the idea of a repeating cycle</p>
	<b>(c)</b>	<p><math>I = Qf</math> or <math>Q = It</math></p> <p><math>f = 3.2 \times 10^{-8} / 9.0 \times 10^{-9} = 3.6</math> (Hz)</p>	<p><b>C1</b></p> <p><b>A1</b></p>	
		<b>Total</b>	<b>12</b>	

Question		Answer	Marks	Guidance
2	(a)	(initial charge) $Q = EC_0$ <b>or</b> ( $Q$ conserved so final) $Q = V(C + C_0)$ (as capacitors are in parallel)	<b>M1</b>	At least one correct expression for $Q$ for first mark
		<u>so</u> $EC_0 = V(C + C_0)$ (and hence $V = C_0 E / (C + C_0)$ )	<b>A1</b>	The two correct expressions equated for the second mark
	(b)	(i)		
		(i)		
		(ii)		
		(i)		
		(ii)		
		(iii)		
		(iii)		
	(c)			
<b>Total</b>			<b>10</b>	


Question			Answer	Marks	Guidance
3	(a)	(i)	$L (= 4\pi r^2 \sigma T^4) = 4 \times \pi \times (7.0 \times 10^8)^2 \times 5.67 \times 10^{-8} \times 5800^4$  $L = 3.95 \times 10^{26} \text{ (W)}$	<b>M1</b>  <b>A0</b>	Mark is for substitution of values <b>Allow</b> $\sigma$ for $5.67 \times 10^{-8}$
		(ii)	By ratios: $25 = 1.7^2 \times (T/5800)^4$   $T^4 = 9.8 \times 10^{15}$  $T = 9950 \text{ (K)}$	<b>C1</b>      <b>C1</b>   <b>A1</b>	<b>or</b> $T^4 = \frac{25L/4\pi\sigma(1.7r)^2}{4\pi \times 5.67 \times 10^{-8} \times (1.7 \times 7 \times 10^8)^2}$ $= \frac{25 \times 3.95 \times 10^{26}}{4\pi \times 5.67 \times 10^{-8} \times (1.7 \times 7 \times 10^8)^2}$  <b>ECF</b> for $L$ in <b>a(i)</b> but only if $L = 4 \times 10^{26}$ to 1s.f. <b>ECF</b> for incorrect $\sigma$ in <b>a(i)</b>  <b>Allow</b> $9.9 \times 10^{15}$ (using $L = 4 \times 10^{26}$ )  <b>Allow</b> 10,000 K
	(b)		see next page	<b>B1 x 6</b>	
<b>Total</b>				<b>10</b>	



Question		Answer	Marks	Guidance
3	(b)	*	B1 x 6	<p><b>Use level of response annotations in RM Assessor, e.g. L2 for 4 marks, L2^ for 3 marks, etc. Indicative scientific points may include:</b></p> <p><b>statement 1</b></p> <ul style="list-style-type: none"> <li>• fusion reactions are occurring</li> <li>• which change H into He</li> <li>• and mass is lost which releases energy</li> <li>• energy released = <math>c^2\Delta m</math></li> <li>• <math>\Delta m</math> per second = luminosity / <math>c^2</math></li> </ul> <p><b>statement 2</b></p> <ul style="list-style-type: none"> <li>• average k.e. of each proton is <math>\frac{3}{2}kT</math></li> <li>• high <math>T</math> means protons are travelling at high speed</li> <li>• so fast enough to overcome repulsive forces</li> <li>• and get close enough to fuse</li> <li>• p.e. = <math>e^2/4\pi\epsilon_0 r</math> so <math>T</math> must be high enough for <math>\frac{3}{2}kT &gt; e^2/4\pi\epsilon_0 r</math></li> <li>• <math>r</math> is approximately 3fm</li> </ul> <p><b>statement 3</b></p> <ul style="list-style-type: none"> <li>• k.e. <math>\propto T</math> so average energy at <math>10^7</math> K is only one thousandth of the average energy at <math>10^{10}</math> K when protons might fuse</li> <li>• but M-B distribution applies so at the high energy end there will be a few p with enough energy</li> <li>• quantum tunnelling across potential barrier is possible</li> <li>• small probability of many favourable collisions to boost energy of p</li> <li>• 4 p must fuse to produce He; it is complicated process making probability of fusion much less</li> <li>• number of p in Sun is so huge that, even with such a small probability, <math>4 \times 10^9</math> kg of p still interact <math>s^{-1}</math></li> <li>• a larger probability means lifetime of the Sun would be shorter</li> </ul>

Question		Answer	Marks	Guidance
4	(a)	There is no contact force between the astronaut and the (floor of the) space station (so no method of measuring / experiencing weight)	B1	Allow astronaut and the space station have same acceleration (towards Earth) / floor is falling (beneath astronaut)
	(b)	(i) $M = 5.97 \times 10^{24}(\text{kg})$ or ISS orbital radius $R = 6.78 \times 10^6(\text{m})$ or $g \propto 1/r^2$  $(gr^2 = \text{constant so}) g \times (6.78 \times 10^6)^2 = 9.81 \times (6.37 \times 10^6)^2$  $g = 8.66 (\text{N kg}^{-1})$	C1  C1 A1	or $g (= GM/R^2) = 6.67 \times 10^{-11} \times 5.97 \times 10^{24} / (6.78 \times 10^6)^2$  Allow rounding of final answer to 2 SF i.e. 8.7 (N kg <sup>-1</sup> )
		(ii) $2\pi r/T = v$ or $T = 2 \times 3.14 \times 6.78 \times 10^6 / 7.7 \times 10^3$  $T = 5.5 \times 10^3 \text{ s } (= 92 \text{ min})$	M1 A1	ECF incorrect value of $R$ from b(i)
	(c)	$\frac{1}{2}Mc^2 (\frac{1}{2}N_A m c^2) = \frac{3}{2}RT$  $c^2 = 3 \times 8.31 \times 293 / 2.9 \times 10^{-2} = 2.52 \times 10^5$  $\sqrt{c^2} = 500 (\text{m s}^{-1})$  $(= 7.7 \times 10^3 / 15)$	C1  C1 A1 A0	or $\frac{1}{2}mc^2 = \frac{3}{2}kT$ or $c^2 = 3kT/m$  or $c^2 = 3 \times 1.38 \times 10^{-23} \times 6.02 \times 10^{23} \times 293 / 2.9 \times 10^{-2} = 2.52 \times 10^5$  not $(7.7 \times 10^3 / 15) = 510 (\text{m s}^{-1})$
	(d)	power reaching cells $(= IA) = 1.4 \times 10^3 \times 2500 = 3.5 \times 10^6 \text{ W}$  power absorbed $= 0.07 \times 3.5 \times 10^6 = 2.45 \times 10^5 \text{ W}$  cells in Sun for $(92 - 35 =) 57$ minutes  average power $= 57/92 \times 2.45 \times 10^5 = 1.5 \times 10^5 (\text{W})$	C1  C1 C1 A1	mark given for multiplication by 0.07 at any stage of calculation  $(90 - 35 =) 55$ minutes using $T = 90$ minutes ECF value of $T$ from b(ii)  $55/90 \times 2.45 \times 10^5 = 1.5 \times 10^5 (\text{W})$ using $T = 90$ minutes
<b>Total</b>			<b>13</b>	

Question		Answer	Marks	Guidance
5	(a)	$c = f\lambda$ or $f = 3.0 \times 10^8 / 0.60$ $f = 5.0 \times 10^8$ (Hz)	C1 A1	Allow $v = f\lambda$ Allow $5 \times 10^8$
	(b)	$a_{max} = -\omega^2 A$ or $a_{max} = -(2\pi f)^2 A$ $\omega = 2 \times \pi \times 5.0 \times 10^8 = 3.1(4) \times 10^9$ (rad s <sup>-1</sup> ) or $10^9\pi$ $a_{max} (= \pi^2 \times 10^{18} \times 4.0 \times 10^{-6}) = 3.9 \times 10^{13}$ (m s <sup>-2</sup> )	C1 C1 A1	Allow without the minus sign ECF from (a) Not $4.0 \times 10^{12}\pi^2$
	(c)	the current (induced in the aerial) is alternating ( $5 \times 10^8$ times per second) (so the meter would register zero) / AW  or the diode (half-)rectifies the current / changes the current (from a.c.) to d.c. / AW	B1	Allow 'a diode only lets current pass through in one direction' AW
	(d)	see next page	B1 x 6	
<b>Total</b>			<b>12</b>	

Question	Answer	Marks	Guidance
5 (d) *	<p><b>Level 3 (5 - 6 marks)</b> Response shows clear distinction between investigations; clear and correct reasoning is given for the situations which give maximum/minimum readings in <u>both</u> cases, including correct numerical values</p> <p><i>There is a well-developed line of reasoning which is clear and logically structured. The information presented is relevant and substantiated.</i></p> <p><b>Level 2 (3 – 4 marks)</b> Response refers to both investigations; some reasoning is given for the situations which give maximum/minimum readings in <u>both</u> investigations, including some numerical values</p> <p><i>There is a line of reasoning presented with some structure. The information presented is in the most part relevant and supported by some evidence.</i></p> <p><b>Level 1 (1 – 2 marks)</b> Limited reasons are given for the situations which give maximum/minimum readings in <u>either</u> investigation</p> <p><i>There is an attempt at a logical structure with a line of reasoning. The information is in the most part relevant.</i></p> <p><b>0 marks</b> <i>No response or no response worthy of credit.</i></p>	B1 x 6	<p><b>Use level of response annotations in RM Assessor, e.g. L2 for 4 marks, L2^ for 3 marks, etc.</b></p> <p><b>Indicative scientific points may include:</b></p> <p><b>explanation 1</b></p> <ul style="list-style-type: none"> <li>• receiver aerial vertical – electrons are driven (maximum distance) up and down along the length of the aerial because the oscillations (of the electric field) are vertical, causing maximum (a.c.) current</li> <li>• receiver aerial horizontal – electrons are driven (minimum distance) across the aerial because the oscillations (of the electric field) are only in the vertical plane (no oscillation along the aerial to cause current), so zero / minimum current</li> <li>• rotation of receiver aerial by <math>\pm 90^\circ</math> (or <math>90^\circ</math> and <math>270^\circ</math>) from vertical leads to zero current</li> </ul> <p><b>explanation 2</b></p> <ul style="list-style-type: none"> <li>• reflected wave superposes with incident wave at receiver aerial</li> <li>• coherent waves as from same source</li> <li>• constructive interference/waves in phase gives max current</li> <li>• reflected wave has travelled <math>n\lambda</math> further, <math>n = 0, 1</math>, etc</li> <li>• so max current when plate is at <math>\lambda/2</math>, <math>2\lambda/2</math>, etc from receiver aerial, i.e. 30, 60 cm</li> <li>• destructive interference/waves <math>180^\circ</math> (<math>\pi</math> rad) out of phase gives zero current</li> <li>• reflected wave has travelled <math>(2n + 1)\lambda/2</math> further, <math>n = 0, 1</math>, etc</li> <li>• so zero current when plate is at <math>\lambda/4</math>, <math>3\lambda/4</math>, etc from receiver aerial, i.e. 15, 45 cm</li> <li>• reflected signal will be weaker the further it has to travel so no longer complete cancellation (ammeter reads close to zero)</li> </ul> <p><b>Note:</b> Give full credit to candidates who take the <math>180^\circ</math> (<math>\pi</math> rad) phase change on reflection into account, which gives max current at 15, 45 cm etc and zero current at 30, 60 cm etc.</p>

Question		Answer	Marks	Guidance
6	(a)		<p><b>B1</b></p> <p><b>B1</b></p>	<p>Path is initially horizontal <b>and</b> further up the page than original</p> <p>Path <u>ends</u> at <math>30^\circ</math> to horizontal (angle must be labelled) in the direction shown</p>
	(b)	$Q = 79e \text{ and } q = 2e$ $F = (1/4\pi\epsilon_0)Qq/r^2$ $= 79 \times 2 \times (1.6 \times 10^{-19})^2 / [4\pi \times 8.85 \times 10^{-12} \times (6.8 \times 10^{-14})^2]$ $= 7.9 \text{ (N)}$	<p><b>C1</b></p> <p><b>C1</b></p> <p><b>C1</b></p> <p><b>A1</b></p>	<p><b>Apply ECF</b> for wrong charge(s), e.g. Q and/or q = e, or Q = 79 and/or q = 2, etc</p>
6	(c)	$(\text{k.e.}) E = 5.0 \times 10^6 \times 1.6 \times 10^{-19}$ $v = \sqrt{2E/m} \text{ or } \sqrt{2 \times 8.0 \times 10^{-13} / 6.6 \times 10^{-27}} = 1.6 \times 10^7 \text{ (ms}^{-1}\text{)}$ $p (= mv) = 6.6 \times 10^{-27} \times 1.6 \times 10^7$ $\text{giving } p = 1.1 \times 10^{-19} \text{ (kg m s}^{-1}\text{)}$	<p><b>C1</b></p> <p><b>C1</b></p> <p><b>A1</b></p>	<p><math>E = 8(.0) \times 10^{-13} \text{ J}</math></p> <p><b>or</b> (<math>E = p^2/2m</math> so) <math>p = \sqrt{2mE}</math></p> <p><b>Note:</b> A value of <math>v = 1.6 \times 10^7 \text{ (ms}^{-1}\text{)}</math> automatically scores both C1 marks even if the calculation for <math>E</math> is not shown</p> <p><b>or</b> <math>p (= \sqrt{2mE}) = \sqrt{2 \times 6.6 \times 10^{-27} \times 8.0 \times 10^{-13}}</math></p> <p>giving <math>p = 1.0 \times 10^{-19} \text{ (kg m s}^{-1}\text{)}</math></p> <p>Full substitution of values must be shown and answer (if calculated) must be correct</p>

6	(d)	(i)	<p>Example (not to scale):</p>  <p><math>p(A)</math></p> <p><math>60^\circ</math></p> <p><math>p(B)</math></p>	<p><b>B1</b></p> <p><b>B1</b></p>	<p>horizontal arrow (judge by eye), in the direction shown</p> <p>arrow drawn at an angle of <math>60^\circ</math> to the horizontal (angle must be shown), in the direction shown</p>
		(ii)	<p>Example (not to scale):</p>  <p><math>60^\circ</math></p> <p>(Can apply principle of) conservation of momentum (since no external forces are acting)</p>	<p><b>B1</b></p> <p><b>B1</b></p>	<p>arrow drawn at an angle of <math>60^\circ</math> to the horizontal (angle must be shown), in the direction shown</p>
<b>Total</b>			<b>13</b>		

**OCR (Oxford Cambridge and RSA Examinations)**  
**The Triangle Building**  
**Shaftesbury Road**  
**Cambridge**  
**CB2 8EA**

**OCR Customer Contact Centre**

**Education and Learning**

Telephone: 01223 553998

Facsimile: 01223 552627

Email: [general.qualifications@ocr.org.uk](mailto:general.qualifications@ocr.org.uk)

[www.ocr.org.uk](http://www.ocr.org.uk)

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored